






FA 10 110 00











P. 1 | 2



● Sternal | ● Dorsal



HS CODE
63072090
CARTON SIZE / PCS.
60 X 40 X 24 cm /12
AET (EU) N°2777/10362-02/E05-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 10 110 00
SIZES	TU
 KG	MAX. 140 KG (VG 11.062 – Rev. 6 - 07/2018)
CE	EN 361:2002, ISO 9150, ISO 15025
Attachment	Dorsal (A), Sternal (A)
	2 / 3
MAT.  / 	
MAT.  45 mm	Aramid
 /  / 	0 / 0 / 0
	1.79 KG

<p> SIZES KG</p> <p>Taille Poids maxi utilisateur Size Max. user weight Tamaño Peso máximo del usuario Dimensione Peso massimo dell'utente Größe Höchstgewicht des Benutzers</p>	<p></p> <p>Nombre de boucles de réglage / boucles automatiques Number of adjustment buckles / automatic buckles Cantidad de hebillas de ajuste / hebillas automáticas Numero di fibbie di regolazione / fibbie autobloccanti Anzahl der Einstellschnallen / Schnellverschluss-Schnallen</p>	<p>MAT.  / </p> <p>Matière dés / boucles Material of rings / buckles Material de anillas en D / hebillas Materia del D / Fibbie Material D-Ringe/Schnallen</p>
<p> /  / </p> <p>Nombre de dés porte-outils / poignées porte-matériel / triangles porte-accessoires Number of tool-holding D-rings/equipment-holding handles/accessory-holding triangles Cantidad de anillas en D portaherramientas / asas portamateriales / triángulos portaccesorios Numero di portautensili / maniglie portamateriale / triangoli portaccesori Anzahl der Werkzeug-D-Ringe / Werkzeug-Halteringe / Zubehör-Triangel</p>		
<p></p> <p>Sangle pouvant résister jusqu'à des températures maximales de 371°C Strap that can withstand temperatures up to 371 °C Correa que puede resistir temperaturas máximas de hasta 371 °C Cinghie possono resistere alle temperature di massimo 371°C Gurt hitzeresistent bis maximal 371°C</p>	<p></p> <p>Sangle pouvant résister à des projections de métal en fusion Strap that can withstand splashes of molten metal Correa que puede resistir proyecciones de metal en fusión Cinghie possono resistere alle proiezioni di metallo in fusione Gurt beständig gegen Spritzer von Schmelzmetall</p>	